



Catalogue 2018

Impact socket kit



SUNSOUL Code

SK-08K

Socket size

22,24,27,30,32,36,38,41

Type

Hexagonal

Surface treatment

Heat treatment & Black coating

Material

CR-MO

Height

80mm

● Features:

- ✘ For 3/4" air impact wrench socket
- ✘ Driven arc angle design, locking force is stronger not easy to skid
- ✘ Forging mould
- ✘ Carbon black phosphating to avoid rusty and oil resistance
- ✘ Completely heated treatment

Impact socket kit



| SUNSOUL Code | SK-10K |
|-------------------|--------------------------------|
| Socket size | 22,24,27,30,32,36,38,41 |
| Type | Hexagonal |
| Surface treatment | Heat treatment & Black coating |
| Material | CR-MO |
| Height | 80mm |

● Features:

- ✘ For 1" air impact wrench socket
- ✘ Driven arc angle design, locking force is stronger not easy to skid
- ✘ Forging mould
- ✘ Carbon black phosphating to avoid rusty and oil resistance
- ✘ Completely heated treatment

Wheel Impact Socket



| SUNSOUL Code | SK-2009 |
|-------------------|-----------------|
| Socket size | 17,19,21,22mm |
| Type | Hexagonal |
| Surface treatment | Nylon Protector |
| Material | CR-MO |
| Height | 80mm |



● Features:

- ※For 1/2" air impact wrench socket
- ※1/2" DRIVE with 6-point hex Opening
- ※High Strenght,High Torque,Less Wear
- ※HD CR-Mo Color-Coded with Dual-HD Sizing Laser & Stamp
- ※With Poly Rim Protectors

Wheel Impact Socket



| SUNSOUL Code | SK-2010 |
|-------------------|------------------------------------|
| Socket size | 9,10,11,12,13,14,17,19,21,22,23,27 |
| Type | Hexagonal |
| Surface treatment | Black coating |
| Material | CR-MO or #45 |
| Height | 38mm |

● Features:

- ※For 1/2" air impact wrench socket
- ※Driven arc angle design,locking force is stronger not easy to skid
- ※Forging mould
- ※Carbon black phosphating to avoid rusty and oil resistance
- ※Completely heated treatment

Wheel Impact Socket



● Features:

- ✘ For 1/2" air impact wrench socket
- ✘ Driven arc angle design, locking force is stronger not easy to skid
- ✘ Forging mould
- ✘ Carbon black phosphating to avoid rusty and oil resistance
- ✘ Completely heated treatment

| SUNSOUL Code | Size(mm) | Height(mm) | Net Weight(g) |
|--------------|----------|------------|---------------|
| SK-2010L-8 | 8 | 78 | 102 |
| SK-2010L-9 | 9 | 78 | 107 |
| SK-2010L-10 | 10 | 78 | 120 |
| SK-2010L-11 | 11 | 78 | 128 |
| SK-2010L-12 | 12 | 78 | 130 |
| SK-2010L-13 | 13 | 78 | 133 |
| SK-2010L-14 | 14 | 78 | 148 |
| SK-2010L-15 | 15 | 78 | 158 |
| SK-2010L-16 | 16 | 78 | 162 |
| SK-2010L-17 | 17 | 78 | 225 |
| SK-2010L-18 | 18 | 78 | 228 |
| SK-2010L-19 | 19 | 78 | 233 |
| SK-2010L-20 | 20 | 78 | 238 |
| SK-2010L-21 | 21 | 78 | 242 |
| SK-2010L-22 | 22 | 78 | 246 |
| SK-2010L-23 | 23 | 78 | 256 |
| SK-2010L-24 | 24 | 78 | 266 |
| SK-2010L-27 | 27 | 78 | 315 |
| SK-2010L-30 | 30 | 78 | 379 |
| SK-2010L-32 | 32 | 78 | 435 |

Wheel Impact Socket



| SUNSOUL Code | SK-2011 |
|-------------------|-------------------------------|
| Socket size | 17,18,19,21,22,23,24,27,29,30 |
| Type | Hexagonal |
| Surface treatment | Black coating |
| Material | CR-MO or #45 |
| Height | 60mm |

● Features:

- ※For 3/4" air impact wrench socket
- ※Driven arc angle design,locking force is stronger not easy to skid
- ※Forging mould
- ※Carbon black phosphating to avoid rusty and oil resistance
- ※Completely heated treatment

Wheel Impact Socket



● Features:

- ✘ For 3/4" air impact wrench socket
- ✘ Driven arc angle design, locking force is stronger not easy to skid
- ✘ Forging mould
- ✘ Carbon black phosphating to avoid rusty and oil resistance
- ✘ Completely heated treatment

| SUNSOUL Code | Size(mm) | SUNSOUL Code | Size(mm) | SUNSOUL Code | Size(mm) |
|--------------|----------|--------------|----------|--------------|----------|
| SK-2011L-17 | 17 | SK-2011L-32 | 32 | SK-2011L-47 | 47 |
| SK-2011L-18 | 18 | SK-2011L-33 | 33 | SK-2011L-48 | 48 |
| SK-2011L-19 | 19 | SK-2011L-34 | 34 | SK-2011L-49 | 49 |
| SK-2011L-20 | 20 | SK-2011L-35 | 35 | SK-2011L-50 | 50 |
| SK-2011L-21 | 21 | SK-2011L-36 | 36 | SK-2011L-52 | 52 |
| SK-2011L-22 | 22 | SK-2011L-37 | 37 | SK-2011L-54 | 54 |
| SK-2011L-23 | 23 | SK-2011L-38 | 38 | SK-2011L-55 | 55 |
| SK-2011L-24 | 24 | SK-2011L-39 | 39 | SK-2011L-56 | 56 |
| SK-2011L-25 | 25 | SK-2011L-40 | 40 | SK-2011L-57 | 57 |
| SK-2011L-26 | 26 | SK-2011L-41 | 41 | SK-2011L-58 | 58 |
| SK-2011L-27 | 27 | SK-2011L-42 | 42 | SK-2011L-59 | 59 |
| SK-2011L-28 | 28 | SK-2011L-43 | 43 | SK-2011L-60 | 60 |
| SK-2011L-29 | 29 | SK-2011L-44 | 44 | SK-2011L-63 | 63 |
| SK-2011L-30 | 30 | SK-2011L-45 | 45 | SK-2011L-65 | 65 |
| SK-2011L-31 | 31 | SK-2011L-46 | 46 | | |

Wheel Impact Socket



| SUNSOUL Code | SK-2012 |
|-------------------|-------------------------------------|
| Socket size | 21,22,24,27,30,32,33,34,35,36,38,41 |
| Type | Hexagonal |
| Surface treatment | Black coating |
| Material | CRV |
| Height | 78mm |

● Features:

- ※For 1" air impact wrench socket
- ※Driven arc angle design,locking force is stronger not easy to skid
- ※Forging mould
- ※Carbon black phosphating to avoid rusty and oil resistance
- ※Completely heated treatment

Wheel Impact Socket



● Features:

- ✘ For 1" air impact wrench socket
- ✘ Driven arc angle design, locking force is stronger not easy to skid
- ✘ Forging mould
- ✘ Carbon black phosphating to avoid rusty and oil resistance
- ✘ Completely heated treatment

| SUNSOUL Code | Size(mm) | Height(mm) | N.W.(g) | SUNSOUL Code | Size(mm) | Height (mm) | N.W.(g) |
|--------------|----------|------------|---------|--------------|----------|-------------|---------|
| SK-2012L-19 | 19 | 90 | 750 | SK-2012L-41 | 41 | 92 | 1120 |
| SK-2012L-20 | 20 | 90 | 787 | SK-2012L-42 | 42 | 92 | 1245 |
| SK-2012L-21 | 21 | 90 | 785 | SK-2012L-43 | 43 | 92 | |
| SK-2012L-22 | 22 | 90 | 785 | SK-2012L-44 | 44 | 92 | |
| SK-2012L-23 | 23 | 90 | 820 | SK-2012L-45 | 45 | 95 | |
| SK-2012L-24 | 24 | 90 | 850 | SK-2012L-46 | 46 | 95 | 1386 |
| SK-2012L-25 | 25 | 90 | 865 | SK-2012L-47 | 47 | 95 | 1375 |
| SK-2012L-26 | 26 | 90 | 830 | SK-2012L-48 | 48 | 95 | |
| SK-2012L-27 | 27 | 90 | 892 | SK-2012L-49 | 49 | 95 | 1450 |
| SK-2012L-28 | 28 | 90 | | SK-2012L-50 | 50 | 95 | 1555 |
| SK-2012L-29 | 29 | 90 | | SK-2012L-52 | 52 | 100 | 1650 |
| SK-2012L-30 | 30 | 90 | 929 | SK-2012L-54 | 54 | 100 | 1720 |
| SK-2012L-32 | 32 | 92 | | SK-2012L-55 | 55 | 100 | 1750 |
| SK-2012L-33 | 33 | 92 | 1080 | SK-2012L-56 | 56 | 100 | |
| SK-2012L-34 | 34 | 92 | 1065 | SK-2012L-57 | 57 | 100 | |
| SK-2012L-35 | 35 | 92 | 1075 | SK-2012L-58 | 58 | 100 | |
| SK-2012L-36 | 36 | 92 | 1090 | SK-2012L-59 | 59 | 100 | |
| SK-2012L-37 | 37 | 92 | | SK-2012L-60 | 60 | 100 | 2065 |
| SK-2012L-38 | 38 | 92 | 1130 | SK-2012L-63 | 63 | 110 | 2530 |
| SK-2012L-39 | 39 | 92 | | SK-2012L-65 | 65 | 110 | 2865 |
| SK-2012L-40 | 40 | 92 | | SK-2012L-70 | 70 | 110 | |

Mounting Rings



| SUNSOUL Code | Description | Diameter |
|--------------|----------------------|----------|
| MR990 | For 13" Rims | 1 3/4" |
| MR991 | For 14" Rims | 1 3/4" |
| MR992 | For 16"-17" Rims | 1 1/8" |
| MR993 | For 19.5" Rims | 1 1/8" |
| MR994 | For 22.5"-24.5" Rims | 1 1/8" |
| MR995 | For 15" Rims | 1 3/4" |
| MR996 | For 16" Rims | 1 3/4" |
| MR997 | For 17" Rims | 1 3/4" |
| MR998 | For 18" Rims | 1 3/4" |
| MR999 | For 20" Rims | 1 3/4" |

● Features:

※Donut-style mounting rings are a simple, yet effective mounting device that fits over the rim between the bead and rim flange creating a seal.

※As the tire expands, the mounting ring slides out over the rim allowing the beads to fully seat.

Mounting L Rings



| SUNSOUL Code | Rim Size | Bag Qty |
|--------------|----------|---------|
| LR225 | 25" | 2 |
| LR229 | 29" | 2 |
| LR233 | 33" | 2 |
| LR235 | 35" | 2 |
| LR239 | 39" | 2 |
| LR245 | 45" | 2 |
| LR249 | 49" | 2 |
| LR251 | 51" | 2 |
| LR257 | 57" | 2 |
| LR263 | 63" | 2 |

● Features:

※Many earthmover, grader, agricultural and industrial tires require the use of O-rings or L-rings to achieve an air-tight seal.

※We supply the highest quality products to meet this need.

Mounting O Rings





| SUNSOUL Code | Tire Type | Rod Diameter | Rim Size | Bag Qty |
|--------------|-------------|--------------|----------|---------|
| OR1220JM | Highway(JM) | 0.250" | 20" | 2 |
| OR1222JM | Highway(JM) | 0.250" | 22" | 2 |
| OR1224JM | Highway(JM) | 0.250" | 24" | 2 |
| OR1220TG | Grader | 0.250" | 20" | 2 |
| OR1224TG | Grader | 0.250" | 24" | 2 |
| OR125T | Earthmover | 0.250" | 25" | 2 |
| OR1325T | Earthmover | 0.375" | 25" | 2 |
| OR1329T | Earthmover | 0.375" | 29" | 2 |
| OR1332T | Earthmover | 0.375" | 32" | 2 |
| OR1333T | Earthmover | 0.375" | 33" | 2 |
| OR1335T | Earthmover | 0.375" | 35" | 2 |
| OR1345T | Earthmover | 0.375" | 45" | 2 |
| OR1349T | Earthmover | 0.375" | 49" | 2 |
| OR1451T | Earthmover | 0.500" | 51" | 2 |
| OR1457T | Earthmover | 0.500" | 57" | 2 |

● Features:

※Many earthmover, grader, agricultural and industrial tires require the use of O-rings or L-rings to achieve an air-tight seal.

※We supply the highest quality products to meet this need.


Impact Bead Breaker

| | SUNSOUL Code | Description | Size | N.w. | Extend Length |
|--|--------------|---|--------|---------|---------------|
|  <p>IBB-1.2 GREEN</p> | IBB-1.2 | Tire impact bar, Green, Orange, Red,Black color | 1200mm | 10.5kgs | 80" |
|  <p>IBB-1.2 BLACK</p> | | | | | |

● Features:

- ✘Loosens bead with bead-breaking foot and rim bar,but never cut the bead of the tire.
- ✘The wedge foot is forced and rim flange.
- ✘No other bead breaking tools are necessary.
- ✘Designed with an exclusive spring action to reduce user fatigue associated with slide hammer kickback.


Tire Mounting & Demounting tools

| | SUNSOUL Code | Description | Size | N.w. |
|--|--------------|-------------------------------|-----------------|-------------|
|  <p>TNT-100</p> | TNT-100 | Tire mounting/demounting tool | 133*34*2 3mm | 13.5 kgs |

● Features:

- ※ Mount all tubeless tires 17.5 thru 24.5
- ※ Not damage beads, saving valuable casings for successful retreading.
- ※ Eliminate the need to lift tire and rim to remove the bottom bead, preventing possible strain or even severe injury.
- ※ Make tire demounting and mounting much more natural.
- ※ Save time a tubeless tire can be demounted in as little as eight seconds and remounted in less than 20 seconds. Super Singles may require additional time.
- ※ Enable some tubeless tires to be demounted and mounted without removing the wheel from the vehicle.



Tire Mounting & Demounting tools

|  | SUNSOUL Code | Description | Size | N.w. |
|---|--------------|-------------------------------|---------|-------------|
| | TL-04 | Tire mounting/demounting tool | 90*20mm | 2.35 kgs |

● Features:

- ✘ Improved shape maintains better rin contact.
- ✘ The wider blade grabs more of the bead.
- ✘ Available with or without the tip on the demount end.
- ✘ Apply to both the tubless tire and tube tire.
- ✘ Forged by 40 chromium steel, chrome coated.

Tyre Ring Opener

| | SUNSOUL Code | Description | Size | N.w. |
|--|--------------|------------------|------------------|------|
|  <p>TRO-110</p> | TRO-110 | Tire ring opener | Length:11 0cm | 6kgs |
|  <p>TRO-120</p> | TRO-120 | Tire ring opener | Length:12 0cm | 7kgs |

● Features:

- ※Mount all tubeless tires 17.5 thru 24.5
- ※Not damage beads, saving valuable casings for successful retreading.
- ※Eliminate the need to lift tire and rim to remove the bottom bead, preventing possible strain or even severe injury.
- ※Not damage beads, saving valuable time for successful removing the wheel ring

Rim Width Caliper



WBW-002



WBW-001

| SUNSOUL Code | Description |
|--------------|--|
| WBW-001 | Rim Width Caliper |
| WBW-002 | Manual Hub Nut for Wheel Balancer for Coarse Thread Shaft 28.5mm |

Balance Wheel weight pliers



| SUNSOUL Code | Description |
|--------------|--|
| T16C | No-Mar Wheel Weight Pliers for Aluminum Rims |
| T16D | Wheel Weight Pliers |

Balance Wheel weight pliers



| SUNSOUL Code | Description |
|--------------|--------------------------------|
| T16A | Heavy-Duty Wheel Weight Pliers |
| T16B | Wheel Weight Pliers |
| T17P | Stick on Wheel Weight Pliers |
| T19W | Premium Wheel Weight Hammer |

Tire Mounting Paste Tool and rim protector



SUNSOUL Code

Description

TMPT18

Large Applicator Brush, 2" Diameter

RP001

Rubber Rim Protector

● Features:

※Tire Mounting Paste Tool and rim protector

Tire Change Tool Tire Lever



SUNSOUL Code

TL-03

Length available

12",16",18",20",24"

Packing

each per polybag

Surface treatment

Chrome

Material

Chrome vanadium

● Features:

- ✘ For all vehicles
- ✘ Bend head is easy to open the rim
- ✘ #45 Chrome vanadium material and strong enough
- ✘ Completely heated treatment

Cross Socket Wrench



| | |
|---------------------|----------------------------|
| SUNSOUL Code | ZQ1020F ZQ1020 |
| Length available | 16",18",20",24" |
| Packing | each per polybag |
| Surface treatment | Chrome |
| Material | Chrome vanadium |
| Socket size | 17-19-21-23 or 17-19-21-24 |

● Features:

- ※For all vechiles
- ※#45 Chrome vadadium material and strong enough
- ※Completely heated treatment
- ※Without clip is available,Item No.: ZQ1020

Cross Socket Wrench



| SUNSOUL Code | ZQ1030 |
|-------------------|-----------------|
| Socket size | 17-19,21-23 |
| Length extension | 360-500 mm |
| Surface treatment | Chrome |
| Material | Chrome vanadium |
| Weight | 1185g |

● Features:

- ※For all vehicles
- ※With protector clip in the middle is more strong
- ※Rough handle part avoid slip
- ※#45 Chrome vanadium material and strong enough
- ※Completely heated treatment



SERVICE WITH A SMILE

86-574-8185 8937
Contact Us

