



Catalogue 2021

Wheel Adapter

A-4 Holes



● Features:

- ※ Meeting with USA, Europe, and Australia market's requirement.
- ※ CNC Machined using 6061 T6 Aerospace Aluminum
- ※ Increasing the car wheel tread, reduce gravity of the body
- ※ 4 holes

| SUNSOU CODE | Vehicle PCD | Wheel PCD | Thickness | ID | OD | Stud Thread Size |
|---------------|-------------|-----------|---------------------|----------|-----|------------------|
| SSWA4100-4100 | 4x100 | 4x100 | 1", 1.25" | 60,64 | 150 | 12x1.5 |
| SSWA4100-4425 | 4x100 | 4x4.25 | 1", 1.25" | 64 | 150 | 12x1.5 |
| SSWA4100-4450 | 4x100 | 4x4.5 | 1", 1.25" | 60,64 | 150 | 12x1.5 |
| SSWA4110-4110 | 4x110 | 4x110 | 1", 1.5", 2" | 73.1, 74 | 150 | 12x1.5 |
| SSWA4110-4450 | 4x110 | 4x4.5 | 1" | 73.1 | 150 | 12x1.5 |
| SSWA4110-4110 | 4x130 | 4x130 | 1" | 78 | 164 | 12x1.5 |
| SSWA4130-4130 | 4x130 | 4x4.5 | 1" | 78 | 164 | 12x1.5 |
| SSWA4130-4450 | 4x156 | 4x156 | 1", 2" | 131 | 202 | 3/8"-24 |
| SSWA4156-4156 | 4x4.25 | 4x100 | 1", 1.25" | 71, 73 | 150 | 12x1.5 |
| SSWA4425-4100 | 4x4.25 | 4x4.25 | 1", 1.25", 1.5" | 71, 73 | 150 | 12x1.5 |
| SSWA4425-4425 | 4x4.25 | 4x5.5 | 1", 1.25" | 73 | 150 | 12x1.5 |
| SSWA4400-4100 | 4x4 | 4x100 | 1" | 64 | 150 | 12x1.5 |
| SSWA4400-4400 | 4x4 | 4x4 | 1" | 64 | 150 | 12x1.5 |
| SSWA4450-4425 | 4x4.5 | 4x4.25 | 1", 1.25" | 73 | 150 | 12x1.5 |
| SSWA4450-4450 | 4x4.5 | 4x4.5 | 1", 1.25", 1.5", 2" | 71, 73 | 150 | 12x1.5 |

Any specification and color can be customized

Wheel Adapter

A-5 Holes



● Features:

- ※Meeting with USA,Europe,and Austrilia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread,reduce gravity of the body
- ※Any specification and color can be customized

| SUNSOUL CODE | Vehicle PCD | Wheel PCD | Thickness | ID | OD | Stud Thread Size |
|---------------|-------------|-----------|------------------|--------------|-----|------------------|
| SSWA5100-5100 | 5x100 | 5x100 | 1",1.25",1.5",2" | 57.1,73.1 | 150 | 12x1.5 |
| SSWA5100-5110 | 5x100 | 5x110 | 1" | 57.1 | 150 | 12x1.5 |
| SSWA5100-5112 | 5x100 | 5x112 | 1",1.25" | 57.1 | 150 | 12x1.5 |
| SSWA5100-5425 | 5x100 | 5x4.25 | 1" | 57.1 | 150 | 12x1.5 |
| SSWA5100-5450 | 5x100 | 5x4.5 | 1",1.25" | 57.1,73.1 | 150 | 12x1.5 |
| SSWA5100-5475 | 5x100 | 5x4.75 | 1" | 57.1,73.1 | 164 | 12x1.5 |
| SSWA5105-5100 | 5x105 | 5x100 | 1" | 56.6 | 150 | 12x1.5 |
| SSWA5105-5110 | 5x105 | 5x100 | 1" | 56.6 | 150 | 12x1.5 |
| SSWA5105-5450 | 5x105 | 5x4.5 | 1" | 56.6 | 150 | 12x1.5 |
| SSWA5110-5110 | 5x110 | 5x100 | 1" | 65.1 | 150 | 12x1.5 |
| SSWA5110-5110 | 5x110 | 5x110 | 1",1.25" | 65.1 | 150 | 12x1.5 |
| SSWA5110-5450 | 5x110 | 5x4.5 | 1",1.25" | 65.1 | 150 | 12x1.5 |
| SSWA5110-5475 | 5x110 | 5x4.75 | 1",1.25" | 65.1 | 164 | 12x1.5 |
| SSWA5115-5115 | 5x115 | 5x115 | 1",1.25",1.5",2" | 57.1,73.1,74 | 150 | 12x1.5,14x1.5 |
| SSWA5115-5450 | 5x115 | 5x4.5 | 1.25" | 74 | 150 | 12x1.5 |
| SSWA5115-5475 | 5x115 | 5x4.75 | 1.25" | 74 | 164 | 12x1.5 |
| SSWA5115-5500 | 5x115 | 5x5 | 1.25" | 74 | 150 | 12x1.5 |
| SSWA5120-5120 | 5x120 | 5x120 | 1",1.25",1.5" | 67.1,72.6 | 164 | 14x1.5 |
| SSWA5135-5135 | 5x135 | 5x135 | 1.5",2" | 87.1 | 176 | 14x2.0 |
| SSWA5135-5450 | 5x135 | 5x4.5 | 1.25",1.5" | 71.5,87.1 | 176 | 14x1.5,14x2.0 |
| SSWA5400-5400 | 5x4 | 5x4 | 1" | 73.1 | 164 | 12x1.5 |
| SSWA5425-5425 | 5x4.25 | 5x4.25 | 1",1.25" | 70.7 | 150 | 12x1.5 |
| SSWA5425-5450 | 5x4.25 | 5x4.5 | 1",1.25" | 70.7,73.1 | 150 | 12x1.5 |
| SSWA5425-5475 | 5x4.25 | 5x4.75 | 1" | 70.7 | 164 | 12x1.5 |

Wheel Adapter

A-6 Holes



● Features:

- ※Meeting with USA,Europe,and Austrilia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread,reduce gravity of the body
- ※Any specification and color can be customized

| SUNSOUL CODE | Vechicle PCD | Wheel PCD | Thickness | ID | OD | Stud Thread Size |
|---------------|--------------|-----------|---------------|----------------|-----|----------------------|
| SSWA6132-6550 | 6x132 | 6x5.5 | 1.5" | 74.5 | 176 | 14x1.5 |
| SSWA6135-6135 | 6x135 | 6x135 | 1.5",2" | 87.1 | 176 | 14x2.0 |
| SSWA6135-6450 | 6x135 | 6x4.5 | 1.25" | 87.1 | 176 | 14x2.0 |
| SSWA6135-6550 | 6x135 | 6x5.5 | 1.5" | 87.1 | 176 | 14x2.0 |
| SSWA6450-6135 | 6x4.5 | 6x135 | 1.25" | 71.5 | 176 | 14x2.0 |
| SSWA6450-6450 | 6x4.5 | 6x4.5 | 1",1.5",2" | 66.1,71.5,73.1 | 150 | 1/2"-20,12x1.25 |
| SSWA6450-6550 | 6x4.5 | 6x5.5 | 1",1.25",1.5" | 71.5,73.1 | 176 | 1/2"-20 |
| SSWA6500-6135 | 6x5 | 6x135 | 1.5" | 78.1 | 176 | 14x2.0 |
| SSWA6500-6500 | 6x5 | 6x5 | 1.5" | 78.3 | 164 | 12x1.5 |
| SSWA6500-6550 | 6x5 | 6x5.5 | 1",1.5" | 78.3 | 176 | 14x1.5 |
| SSWA6550-6115 | 6x5.5 | 6x115 | 1.5" | 78.1 | 176 | 12x1.5 |
| SSWA6550-6120 | 6x5.5 | 6x120 | 1.5" | 65.1 | 176 | 12x1.5 |
| SSWA6550-6127 | 6x5.5 | 6x127 | 1.5" | 78.1 | 176 | 12x1.5 |
| SSWA6550-6132 | 6x5.5 | 6x132 | 1.5" | 78.1 | 176 | 12x1.5 |
| SSWA6550-6135 | 6x5.5 | 6x135 | 1.25",1.5" | 78.1,108 | 176 | 12x1.5,14x1.5,14x2.0 |
| SSWA6550-6450 | 6x5.5 | 6x4.5 | 1.5" | 78.1,87.1 | 176 | 14x1.5 |
| SSWA6550-6500 | 6x5.5 | 6x5 | 1.5" | 78.1 | 176 | 12x1.5 |

Wheel Adapter

A-8 Holes



● Features:

- ※Meeting with USA,Europe,and Austrilia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread,reduce gravity of the body
- ※Any specification and color can be customozied

| SUNSOU L CODE | Vehicle PCD | Wheel PCD | Thickness | ID | OD | Stud Thread Size |
|---------------|-------------|-----------|--------------------|---------------|-----|----------------------|
| SSWA8170-8170 | 8x170 | 8x170 | 1.5",2",2.5",3" | 108,125,125.6 | 202 | 14x1.5,14x2.0 |
| SSWA8170-8180 | 8x170 | 8x180 | 1.5" | 125.6 | 215 | 14x1.5 |
| SSWA8170-8200 | 8x170 | 8x200 | 2" | 125 | 254 | 14x1.5 |
| SSWA8170-8650 | 8x170 | 8x6.5 | 1.5",2" | 125,125.6 | 202 | 14x1.5 |
| SSWA8180-8180 | 8x180 | 8x180 | 1.5",2",2.5",3" | 125.6 | 215 | 14x1.5 |
| SSWA8180-8210 | 8x180 | 8x210 | 2" | 125.6 | 254 | 14x1.5 |
| SSWA8180-8650 | 8x180 | 8x6.5 | 1.5",2" | 125.6 | 215 | 14x1.5 |
| SSWA8200-8200 | 8x200 | 8x200 | 2" | 146 | 254 | 14x1.5 |
| SSWA8210-8210 | 8x210 | 8x210 | 2",2.5" | 155 | 254 | 14x1.5 |
| SSWA8650-8170 | 8x6.5 | 8x170 | 1.5",2" | 125.6,126 | 202 | 14x1.5 |
| SSWA8650-8180 | 8x6.5 | 8x180 | 1.5",2" | 125.6,126 | 216 | 14x1.5 |
| SSWA8650-8650 | 8x6.5 | 8x6.5 | 1",1.5",2",2.5",3" | 125.6,126 | 202 | 14x1.5,9/16",1/2"-20 |

Wheel Adapter

B-Double Drilled 1 Piece



● Features:

- ✘ Meeting with USA, Europe, and Australia market's requirement.
- ✘ CNC Machined using 6061 T6 Aerospace Aluminum
- ✘ Increasing the car wheel tread, reduce gravity of the body
- ✘ Any specification and color can be customized

| SUNSOUL CODE | Vehicle | Wheel PCD | Thickness | ID | OD | Stud Thread Size |
|--------------------|--------------|-----------|-----------|------|-----|------------------|
| SSWA4100/4425-4450 | 4x100/4x4.25 | 4x4.5 | 1" | 71 | 150 | 12x1.5 |
| SSWA4100/4450-4425 | 4x100/4x4.5 | 4x4.25 | 1" | 71 | 150 | 12x1.5 |
| SSWA4425/4450-4100 | 4x4.25/4x4.5 | 4x100 | 1" | 71 | 150 | 12x1.5 |
| SSWA4425/4450-4425 | 4x4.25/4x4.5 | 4x4.25 | 1" | 67.1 | 150 | 12x1.5 |
| SSWA5135/5500-5135 | 5x135/5x5 | 5x135 | 1.5" | 87.1 | 176 | 12x1.5 |
| SSWA5135/5500-5450 | 5x135/5x5 | 5x4.5 | 1.5" | 87.1 | 176 | 12x1.5 |
| SSWA5135/5500-5475 | 5x135/5x5 | 5x4.75 | 1.5" | 87.1 | 176 | 12x1.5 |
| SSWA5135/5500-5500 | 5x135/5x5 | 5x5 | 1.5" | 87.1 | 176 | 12x1.5 |
| SSWA5135/5500-5550 | 5x135/5x5 | 5x5.5 | 1.5" | 87.1 | 176 | 12x1.5 |
| SSWA5450/5475-5110 | 5x4.5/5x4.75 | 5x110 | 1.25" | 74 | 164 | 12x1.5 |
| SSWA5450/5475-5112 | 5x4.5/5x4.75 | 5x112 | 1.25" | 74 | 164 | 12x1.5 |
| SSWA5450/5475-5115 | 5x4.5/5x4.75 | 5x115 | 1.25" | 74 | 164 | 12x1.5 |

Wheel Adapter

B-Double Drilled 1 Piece



● Features:

- ✘ Meeting with USA, Europe, and Australia market's requirement.
- ✘ CNC Machined using 6061 T6 Aerospace Aluminum
- ✘ Increasing the car wheel tread, reduce gravity of the body
- ✘ Any specification and color can be customized

| SUNSOUL CODE | Vehicle | Wheel PCD | Thickness | ID | OD | Stud Thread Size |
|--------------------|--------------|-----------|-----------|------|-----|------------------|
| SSWA5450/5475-5135 | 5x4.5/5x4.75 | 5x135 | 1.25" | 74 | 176 | 12x1.5 |
| SSWA5450/5475-5450 | 5x4.5/5x4.75 | 5x4.5 | 1.25" | 74 | 164 | 12x1.5 |
| SSWA5450/5475-5475 | 5x4.5/5x4.75 | 5x4.75 | 1.25" | 74 | 164 | 12x1.5 |
| SSWA5450/5475-5500 | 5x4.5/5x4.75 | 5x5 | 1.25" | 74 | 164 | 12x1.5 |
| SSWA5450/5475-5550 | 5x4.5/5x4.75 | 5x5.5 | 1.25" | 74 | 176 | 12x1.5 |
| SSWA5475/5500-5500 | 5x4.75/5x5 | 5x5 | 1.5" | 78.1 | 164 | 12x1.5 |
| SSWA5500/5550-5135 | 5x5/5x5.5 | 5x135 | 1.5" | 87.1 | 176 | 1/2"-20 |
| SSWA5500/5550-5450 | 5x5/5x5.5 | 5x4.5 | 1.5" | 87.1 | 176 | 1/2"-20 |
| SSWA5500/5550-5475 | 5x5/5x5.5 | 5x4.75 | 1.5" | 87.1 | 176 | 1/2"-20 |
| SSWA5500/5550-5500 | 5x5/5x5.5 | 5x5 | 1.5" | 87.1 | 176 | 1/2"-20 |
| SSWA5500/5550-5550 | 5x5/5x5.5 | 5x5.5 | 1.5" | 87.1 | 176 | 1/2"-20 |

Wheel Adapter

B-Double Drilled 2 Pieces



● Features:

- ✘ Meeting with USA, Europe, and Australia market's requirement.
- ✘ CNC Machined using 6061 T6 Aerospace Aluminum
- ✘ Increasing the car wheel tread, reduce gravity of the body

| SUNSOUL CODE | THICKNESS | FROM | TO | I.D. | O.D. | THREAD |
|--------------|-----------|--------------|--------|--------|-------|---------|
| SS-20271 | 1.5" | 4*4.25"/4.5" | 5*100 | 71MM | 152MM | M12*1.5 |
| SS-20272 | 1.75" | 5*5.5/4.5" | 4*4.5" | 78MM | 176MM | M12*1.5 |
| SS-20273 | 1.75" | 6*5.5"/5.5" | 5*4.5" | 87.1MM | 176MM | M12*1.5 |
| SS-20274 | 2" | 6*5.5"/5.5" | 5*5.5" | 78.1MM | 176MM | M12*1.5 |

Wheel Adapter

B-Single Drilled 2 pieces



● Features:

- ✧ Meeting with USA, Europe, and Australia market's requirement.
- ✧ CNC Machined using 6061 T6 Aerospace Aluminum
- ✧ Increasing the car wheel tread, reduce gravity of the body

| SUNSOUL CODE | THICKNESS | FROM | TO | I.D. | O.D. | THREAD |
|--------------|-----------|--------|--------|--------|-------|---------|
| SS-20268 | 1" | 4*4.5" | 5*100 | 71MM | 152MM | M12*1.5 |
| SS-20269 | 1.5" | 5*5.5" | 6*4.5" | 87.1MM | 176MM | M12*1.5 |
| SS-20270 | 1.75" | 6*5.5" | 5*4.5" | 87.1MM | 176MM | M12*1.5 |

Wheel Adapter

D-Hub Centric Wheel Adapter



● Features:

- ※ Meeting with USA, Europe, and Australia market's requirement.
- ※ CNC Machined using 6061 T6 Aerospace Aluminum
- ※ Increasing the car wheel tread, reduce gravity of the body

| SUNSOUL CODE | THICKNESS | FROM | TO | I.D. | O.D. | THREAD |
|--------------|-----------|-------|-------|---------|-------|---------|
| SS-20279 | 1.25" | 5*4.5 | 5*4.5 | 71.5MM | 150MM | 1/2-20 |
| SS-20280 | 1.25" | 5*5 | 5*5 | 71.5MM | 164MM | 1/2-20 |
| SS-20281 | 33MM | 5*5.5 | 5*5.5 | 71.6MM | 176MM | 1/2-20 |
| SS-20282 | 1.5" | 5*5.5 | 5*5.5 | 106.5MM | 176MM | 1/2-20 |
| SS-20283 | 1.25" | 5*5.5 | 5*5.5 | 106.5MM | 176MM | 1/2-20 |
| SS-20284 | 30MM | 5*120 | 5*120 | 72.6MM | 164MM | M14*1.5 |
| SS-20285 | 25MM | 5*130 | 5*130 | 71.6MM | 167MM | M14*1.5 |

Wheel Adapter

Porsche(Special)



● Features:

- ※Meeting with USA,Europe,and Austrilia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread,reduce gravity of the body

| SUNSOUL CODE | THICK | VEHICLE FROM | WHEEL TO | C.B. | O.D. | THREAD |
|--------------|-------|--------------|----------|--------|-------|--------|
| SS-10497 | 8MM | 5*130 | 5*130 | 71.6MM | 170MM | 14*1.5 |
| SS-10498 | 9MM | 5*130 | 5*130 | 71.6MM | 170MM | 14*1.5 |
| SS-10499 | 10MM | 5*130 | 5*130 | 71.6MM | 170MM | 14*1.5 |

Wheel Adapter

Wheel Adapter-Special Style



● Features:

- ✘ Meeting with USA, Europe, and Australia market's requirement.
- ✘ CNC Machined using 6061 T6 Aerospace Aluminum
- ✘ Increasing the car wheel tread, reduce gravity of the body

| SUNSOUL CODE | THICK | FROM | TO | C.B. | THREAD |
|--------------|-------|---------|---------|--------|---------|
| SS-20286 | 15MM | 5*112 | 5*112 | 66.6MM | 12*1.5 |
| SS-20287 | 25MM | 5*114.3 | 5*114.3 | 66.6MM | 12*1.5 |
| SS-20288 | 25MM | 5*100 | 5*100 | 54.1MM | 12*1.5 |
| SS-20289 | 25MM | 5*114.3 | 5*114.3 | 60.1MM | 12*1.25 |
| SS-20290 | 25MM | 4*100 | 4*100 | 57.1MM | 12*1.5 |
| SS-20291 | 25MM | 4*108 | 4*108 | 63.4MM | 12*1.5 |
| SS-20292 | 25MM | 5*108 | 5*108 | 65.1MM | 12*1.25 |
| SS-20293 | 25MM | 5*108 | 5*108 | 60.1MM | 14*1.5 |
| SS-20294 | 25MM | 5*112 | 5*112 | 57.1MM | 14*1.5 |
| SS-20295 | 25MM | 5*120 | 5*120 | 72.6MM | 12*1.5 |

Wheel Adapter

Type E1, Type E2, Type E3



● Features:

- ※Meeting with USA, Europe, and Australia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread, reduce gravity of the body

| SUNSOUL CODE | THICK | WHEEL TO | C.B. | O.D. | THREAD | PACK |
|--------------|-------|----------|--------|-------|---------|-----------|
| SS-10313 | 20MM | 4*98 | 58.6MM | 139MM | 12*1.25 | 1pair/box |
| SS-10314 | 25MM | 4*98 | 58.6MM | 139MM | 12*1.25 | 1pair/box |
| SS-10315 | 10MM | 4*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10316 | 12MM | 4*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10317 | 15MM | 4*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10318 | 16MM | 4*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10319 | 20MM | 4*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10320 | 25MM | 4*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10321 | 10MM | 4*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10322 | 12MM | 4*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10323 | 15MM | 4*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10324 | 16MM | 4*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10325 | 20MM | 4*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10326 | 25MM | 4*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10327 | 10MM | 4*108 | 57.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10328 | 12MM | 4*108 | 57.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10329 | 15MM | 4*108 | 57.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10330 | 16MM | 4*108 | 57.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10331 | 20MM | 4*108 | 57.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10332 | 15MM | 4*108 | 63.3MM | 149MM | 12*1.5 | 1pair/box |
| SS-10333 | 20MM | 4*108 | 63.3MM | 149MM | 12*1.5 | 1pair/box |
| SS-10334 | 15MM | 4*108 | 70.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10335 | 20MM | 4*108 | 70.1MM | 149MM | 12*1.5 | 1pair/box |

Wheel Adapter

Type F1



● Features:

- ✘ Meeting with USA, Europe, and Australia market's requirement.
- ✘ CNC Machined using 6061 T6 Aerospace Aluminum
- ✘ Increasing the car wheel tread, reduce gravity of the body

| SUNSOUL CODE | THICKNESS | FROM | WHEEL TO | C.B. | O.D. | THREAD |
|--------------|-----------|------|----------|--------|-------|---------|
| SS-10336 | 10MM | 4*98 | 4*98 | 58.1MM | 139MM | 12*1.25 |
| SS-10337 | 12MM | 4*98 | 4*98 | 58.1MM | 139MM | 12*1.25 |
| SS-10338 | 15MM | 4*98 | 4*98 | 58.1MM | 139MM | 12*1.25 |
| SS-10339 | 20MM | 4*98 | 4*98 | 58.1MM | 139MM | 12*1.25 |
| SS-10340 | 25MM | 4*98 | 4*98 | 58.1MM | 139MM | 12*1.25 |
| SS-10341 | 10MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.25 |
| SS-10342 | 12MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.25 |
| SS-10343 | 15MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.25 |
| SS-10344 | 16MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.25 |
| SS-10345 | 20MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.25 |
| SS-10346 | 25MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.25 |
| SS-10347 | 10MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.5 |
| SS-10348 | 12MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.5 |
| SS-10349 | 15MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.5 |
| SS-10350 | 16MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.5 |
| SS-10351 | 20MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.5 |
| SS-10352 | 25MM | 4*98 | 4*98 | 58.6MM | 139MM | 12*1.5 |

Wheel Adapter

Type G1,G2



● Features:

- ※Meeting with USA, Europe, and Australia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread, reduce gravity of the body

| SUNSOU CODE | THICKNESS | WHEEL TO | C.B. | O.D. | THREAD | PACK |
|-------------|-----------|----------|--------|-------|---------|-----------|
| SS-10367 | 10MM | 5*98 | 58.1MM | 139MM | 12*1.25 | 1pair/box |
| SS-10368 | 12MM | 5*98 | 58.1MM | 139MM | 12*1.25 | 1pair/box |
| SS-10369 | 15MM | 5*98 | 58.1MM | 139MM | 12*1.25 | 1pair/box |
| SS-10370 | 16MM | 5*98 | 58.1MM | 139MM | 12*1.25 | 1pair/box |
| SS-10371 | 20MM | 5*98 | 58.1MM | 139MM | 12*1.25 | 1pair/box |
| SS-10372 | 25MM | 5*98 | 58.1MM | 139MM | 12*1.25 | 1pair/box |
| SS-10373 | 10MM | 5*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10374 | 12MM | 5*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10375 | 15MM | 5*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10376 | 16MM | 5*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10377 | 20MM | 5*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10378 | 25MM | 5*98 | 58.6MM | 139MM | 12*1.5 | 1pair/box |
| SS-10379 | 10MM | 5*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10380 | 12MM | 5*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10381 | 15MM | 5*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10382 | 16MM | 5*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10383 | 20MM | 5*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10384 | 25MM | 5*100 | 57.1MM | 139MM | 12*1.5 | 1pair/box |
| SS-10385 | 10MM | 5*100 | 57.1MM | 139MM | 14*1.5 | 1pair/box |
| SS-10386 | 12MM | 5*100 | 57.1MM | 139MM | 14*1.5 | 1pair/box |
| SS-10387 | 15MM | 5*100 | 57.1MM | 139MM | 14*1.5 | 1pair/box |
| SS-10388 | 16MM | 5*100 | 57.1MM | 139MM | 14*1.5 | 1pair/box |
| SS-10389 | 20MM | 5*100 | 57.1MM | 139MM | 14*1.5 | 1pair/box |
| SS-10390 | 25MM | 5*100 | 57.1MM | 139MM | 14*1.5 | 1pair/box |
| SS-10391 | 10MM | 5*108 | 58.1MM | 149MM | 12*1.25 | 1pair/box |
| SS-10392 | 12MM | 5*108 | 58.1MM | 149MM | 12*1.25 | 1pair/box |
| SS-10393 | 15MM | 5*108 | 58.1MM | 149MM | 12*1.25 | 1pair/box |
| SS-10394 | 16MM | 5*108 | 58.1MM | 149MM | 12*1.25 | 1pair/box |
| SS-10395 | 20MM | 5*108 | 58.1MM | 149MM | 12*1.25 | 1pair/box |
| SS-10396 | 25MM | 5*108 | 58.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10397 | 10MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10398 | 12MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10399 | 13MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10400 | 15MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10401 | 20MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10402 | 25MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10403 | 30MM | 5*112 | 57.1MM | 149MM | 14*1.5 | 1pair/box |
| SS-10404 | 15MM | 5*120 | 70.5MM | 149MM | 12*1.5 | 1pair/box |

Wheel Adapter

Type G1,G2



● Features:

- ※Meeting with USA,Europe,and Austrilia market's requirement.
- ※CNC Machined using 6061 T6 Aerospace Aluminum
- ※Increasing the car wheel tread,reduce gravity of the body

| SUNSOU CODE | THICKNESS | WHEEL TO | C.B. | O.D. | THREAD | PACK |
|-------------|-----------|----------|---------|-------|---------|-----------|
| SS-10405 | 10MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10406 | 11MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10407 | 12MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10408 | 13MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10409 | 15MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10410 | 16MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10411 | 18MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10412 | 20MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10413 | 25MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10414 | 30MM | 5*120 | 72.6MM | 149MM | 12*1.5 | 1pair/box |
| SS-10415 | 10MM | 5*120 | 74.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10416 | 12MM | 5*120 | 74.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10417 | 15MM | 5*120 | 74.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10418 | 16MM | 5*120 | 74.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10419 | 20MM | 5*120 | 74.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10420 | 25MM | 5*120 | 74.1MM | 149MM | 12*1.5 | 1pair/box |
| SS-10421 | 12MM | 5*120 | 72.6MM | 149MM | 14*1.5 | 1pair/box |
| SS-10422 | 13MM | 5*120 | 72.6MM | 149MM | 14*1.5 | 1pair/box |
| SS-10423 | 15MM | 5*120 | 72.6MM | 149MM | 14*1.5 | 1pair/box |
| SS-10424 | 18MM | 5*120 | 72.6MM | 149MM | 14*1.5 | 1pair/box |
| SS-10425 | 20MM | 5*120 | 72.6MM | 149MM | 14*1.5 | 1pair/box |
| SS-10426 | 25MM | 5*120 | 72.6MM | 149MM | 14*1.5 | 1pair/box |
| SS-10427 | 10MM | 5*120 | 71.6MM | 170MM | 14*1.5 | 1pair/box |
| SS-10428 | 15MM | 5*130 | 71.6MM | 170MM | 14*1.5 | 1pair/box |
| SS-10429 | 5MM | 5*139.7 | 110.5MM | 178MM | 12*1.25 | 1pair/box |

Wheel Adapter

Type H1



● Features:

- ※ Meeting with USA, Europe, and Australia market's requirement.
- ※ CNC Machined using 6061 T6 Aerospace Aluminum
- ※ Increasing the car wheel tread, reduce gravity of the body

| SUNSOU CODE | THICKNESS | Vehicle Form | Wheel to | C.B. | O.D. | THREAD |
|-------------|-----------|--------------|----------|--------|-------|---------|
| SS-10452 | 20MM | 5*100 | 5*100 | 57.1MM | 139MM | 14*1.5 |
| SS-10453 | 25MM | 5*100 | 5*100 | 57.1MM | 149MM | 12*1.25 |
| SS-10454 | 10MM | 5*108 | 5*108 | 58.1MM | 149MM | 12*1.25 |
| SS-10455 | 12MM | 5*108 | 5*108 | 58.1MM | 149MM | 12*1.25 |
| SS-10456 | 15MM | 5*108 | 5*108 | 58.1MM | 149MM | 12*1.25 |
| SS-10457 | 16MM | 5*108 | 5*108 | 58.1MM | 149MM | 12*1.25 |
| SS-10458 | 20MM | 5*108 | 5*108 | 58.6MM | 149MM | 12*1.25 |
| SS-10459 | 25MM | 5*108 | 5*108 | 58.6MM | 149MM | 14*1.5 |
| SS-10460 | 10MM | 5*112 | 5*112 | 57.1MM | 149MM | 14*1.5 |
| SS-10461 | 12MM | 5*112 | 5*112 | 57.1MM | 149MM | 14*1.5 |
| SS-10462 | 13MM | 5*112 | 5*112 | 57.1MM | 149MM | 14*1.5 |
| SS-10463 | 15MM | 5*112 | 5*112 | 57.1MM | 149MM | 14*1.5 |
| SS-10464 | 20MM | 5*112 | 5*112 | 57.1MM | 149MM | 14*1.5 |
| SS-10465 | 25MM | 5*112 | 5*112 | 57.1MM | 149MM | 14*1.5 |
| SS-10466 | 30MM | 5*112 | 5*112 | 57.1MM | 149MM | 12*1.5 |
| SS-10467 | 15MM | 5*120 | 5*120 | 70.5MM | 149MM | 12*1.5 |
| SS-10468 | 10MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10469 | 11MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10470 | 12MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10471 | 13MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10472 | 15MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10473 | 16MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10474 | 18MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10475 | 20MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10476 | 25MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |
| SS-10477 | 30MM | 5*120 | 5*120 | 72.6MM | 149MM | 12*1.5 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-----------------------|------------|------------|
| SS-50100 | 3/5/6/8 | 4&5 Holes on 98-120mm | 78 | 151 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|--------------------------|------------|------------|
| SS-50101 | 8 | 4 Holes on 101.6-114.3mm | 71.5 | 151.5 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|------------------------|------------|------------|
| SS-50102 | 7.8 | 5 Holes on 114.3-127mm | 90 | 164.3 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-------------------|------------|------------|
| SS-50103 | 5.8 | 5&6 Holes on5 1/2 | 107 | 178 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|--------------------|------------|------------|
| SS-50104 | 6/8/10/12 | 8 Holes on 165.1mm | 125 | 207.8 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|----------------------|------------|------------|
| SS-50105 | 8 | 5 Holes on 100-120mm | 81 | 152 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|----------------------|------------|------------|
| SS-50106 | 5 | 5 Holes on 100-120mm | 81 | 152 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|----------------------|------------|------------|
| SS-50108 | 12.7 | 5 Holes on 108-120mm | 82 | 155 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-----------------------|------------|------------|
| SS-50109 | 4/5/7 | 4&5 Holes on 98-120mm | 73 | 148.5 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-----------------------|------------|------------|
| SS-50110 | 3/5/6.35/8/9 | 5&6 Holes on 98*130mm | 72.5 | 152 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-----------------------|------------|------------|
| SS-50111 | 3.5 | 4&5 Holes on 98-120mm | 77 | 143 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-------------------------------------|------------|------------|
| SS-50112 | 6 | 4 Holes on 98-120mm,3-3/4,to 4-1/2" | 72.5 | 157 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|------------------------|------------|------------|
| SS-50113 | 3/5/8 | 4&5Holes on 98-114.3mm | 75 | 135 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|------------------|------------|------------|
| SS-50118 | 6 | 7 Holes on 150mm | 114.3 | 183 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|--------------------|------------|------------|
| SS-50119 | 6 | 6 Holes on 139.7mm | 110 | 168 |

Wheel Spacer



● Features:

- ※Progress: Casting
- ※Material: Aluninum
- ※Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-------------|------------|------------|
| SS-50121 | 12/15 | | 73 | 145 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-------------|------------|------------|
| SS-50122 | 10/15/20/25 | | 72.6 | 141 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-------------|------------|------------|
| SS-50123 | 10/18 | | 73.1 | 141 |

Wheel Spacer



● Features:

- ✘Progress: Casting
- ✘Material: Aluninum
- ✘Treatment: Silver coating

| SUNSOUL CODE | THICKNESS MM | DESCRIPTION | I.D. MM | O.D. MM |
|--------------|-----------------|-------------|------------|------------|
| SS-50124 | 17/20 | | 50 | 150 |

Wheel center hub ring



● Features:

- ※Material: Aluminum
- ※2pcs/bag



● Features:

- ※Material: PE/PP or Nylon
- ※2pcs/bag

| SUNSOU CODE | O.D.Φ | I.D.Φ |
|-------------|--------|--------|
| HR6710-5410 | 67.1MM | 54.1MM |
| HR6710-5610 | 67.1MM | 56.1MM |
| HR6710-5660 | 67.1MM | 56.6MM |
| HR6710-5710 | 67.1MM | 57.1MM |
| HR6710-6006 | 67.1MM | 60.1MM |
| HR6710-6410 | 67.1MM | 64.1MM |
| HR7260-5610 | 72.6MM | 56.1MM |
| HR7260-5710 | 72.6MM | 57.1MM |
| HR7260-5960 | 72.6MM | 59.6MM |
| HR7260-6006 | 72.6MM | 60.1MM |
| HR7260-6390 | 72.6MM | 63.9MM |
| HR7260-6410 | 72.6MM | 64.1MM |
| HR7260-6510 | 72.6MM | 65.1MM |
| HR7260-6606 | 72.6MM | 66.1MM |
| HR7260-6650 | 72.6MM | 66.5MM |
| HR7260-6656 | 72.6MM | 66.6MM |
| HR7260-6710 | 72.6MM | 67.1MM |
| HR1080-6710 | 108MM | 67.1MM |
| HR1080-7810 | 108MM | 78.1MM |
| HR1080-1000 | 108MM | 100MM |
| HR1110-5410 | 110MM | 54.1MM |
| HR1110-6710 | 110MM | 67.1MM |
| HR1110-7810 | 110MM | 78.1MM |

| SUNSOU CODE | O.D.Φ | I.D.Φ |
|-------------|-------|--------|
| HR73-6510 | 73MM | 65.1MM |
| HR73-6610 | 73MM | 66.1MM |
| HR73-6640 | 73MM | 66.4MM |
| HR73-6656 | 73MM | 66.6MM |
| HR73-6710 | 73MM | 67.1MM |
| HR73-7010 | 73MM | 70.1MM |
| HR73-7030 | 73MM | 70.3MM |
| HR73-7050 | 73MM | 70.5MM |
| HR73-7160 | 73MM | 71.6MM |
| HR74-5610 | 74MM | 56.1MM |
| HR74-5710 | 74MM | 57.1MM |
| HR74-6010 | 74MM | 60.1MM |
| HR74-6390 | 74MM | 63.9MM |
| HR74-6410 | 74MM | 64.1MM |
| HR74-6606 | 74MM | 66.1MM |
| HR74-6710 | 74MM | 67.1MM |
| HR74-7010 | 74MM | 70.1MM |
| HR74-7030 | 74MM | 70.3MM |
| HR74-7160 | 74MM | 71.6MM |
| HR74-7260 | 74MM | 72.6MM |
| HR78-6606 | 78MM | 66.1MM |
| HR78-6656 | 78MM | 66.6MM |



SERVICE WITH A SMILE

86-574-8185 8937
Contact Us

